



THIN SHEET NUT-INSERT

JAK-I SERIES

- Knurled Body

Material: Low Carbon Steel

Finish: Zinc Clear Plating Cr3+



▼COUNTERSUNK

Unit: mm

ITEM NO.	THREAD SIZE	GRIP RANGE	HOLE SIZE +0.1	D +0.05/-0.15	H ±0.38	T ±0.1	TL ±0.40
JAK S6-32	6-32	0.5~2.0	6.75	6.70	7.85	0.50	11.10
JAK S6-32-L		2.0~3.3					12.40
JAK S8-32	8-32	0.5~2.0	6.75	6.70	7.85	0.50	11.10
JAK S8-32-L		2.0~3.3					12.40
JAK S10-24(32)	10-24 or	0.5~3.3	7.60	7.50	8.65	0.50	12.50
JAK S10-24(32)-L	10-32	3.3~5.7					15.30
JAK S1/4-20	1/4-20	0.7~4.2	10.00	9.90	11.60	0.55	15.30
JAK S1/4-20-L		4.2~6.6					17.80
JAK S5/16-18	5/16-18	0.7~3.8	13.50	13.45	15.10	0.55	18.00
JAK S5/16-18-L		3.8~7.9					21.00
JAK S3/8-16	3/8-16	0.7~3.8	13.50	13.45	15.10	0.55	18.00
JAK S3/8-16-L		3.8~7.9					21.00

▼LARGE FLANGE

Unit: mm

ITEM NO.	THREAD SIZE	GRIP RANGE	HOLE SIZE +0.1	D +0.05/-0.15 *-0.15	H ±0.38 *±0.64	T ±0.1	TL ±0.40
JAK L6-32	6-32	0.5~2.0	6.75	6.70	9.90	0.75	11.45
JAK L6-32-L		2.0~3.3					12.70
JAK L8-32	8-32	0.5~2.0	6.75	6.70	9.90	0.75	11.45
JAK L8-32-L		2.0~3.3					12.70
JAK L10-24(32)	10-24 or	0.5~3.3	7.60	7.50	10.55	0.75	12.85
JAK L10-24(32)-L	10-32	3.3~5.7					15.50
JAK L1/4-20	1/4-20	0.7~4.2	10.00	9.90	12.70	0.75	15.50
JAK L1/4-20-L		4.2~6.6					18.00
JAK L5/16-18	5/16-18	0.7~3.8	13.50	13.45	*17.40	0.90	18.40
JAK L5/16-18-L		3.8~7.9					21.35
JAK L3/8-16	3/8-16	0.7~3.8	13.50	13.45	*17.40	0.90	18.40
JAK L3/8-16-L		3.8~7.9					21.35
*JAK L1/2-13	1/2-13	1.6~5.1	17.45	*17.40	22.00	1.20	30.40
*JAK L1/2-13-L		5.1~8.9					34.20
*JAK L1/2-13-2L		8.9~12.7					38.00

**MOQ is required.

**Material in aluminum alloy is available with MOQ.

EDC 金開股份有限公司 Energetic Development Corp.

Head office: 5F, No. 1, Lane 50, Sec. 3, Nan Kang Rd., Taipei 115, Taiwan

Tel: (02) 27881122 Fax: (02) 27881480 Website: www.edccorp.com.tw Email: edc@edccp.com